

FUJITSU M10-4 SERVER

MAINFRAME RELIABILITY WITH INDUSTRY-LEADING VIRTUALIZATION

KEY FEATURES

- This server provides a compact footprint with high performance and reliability.
- It scales up to 64 cores.
- It is ideal for data center integration and virtualization.
- The new 2.8 GHz SPARC64 X processor, with supercomputer technology, provides superior performance for enterprise workloads such as OLTP, ERP, BIDW, SCM, and CRM.
- Software-on-chip instructions on the SPARC64 X processor accelerate key database functions.
- The CPU Activation feature economically and rapidly meets capacity requirements.
- Flexible resource configuration using Oracle VM Server for SPARC and Oracle Solaris Zones virtualization technologies.
- Power-saving features are built into the processor and the server.
- This server features mainframe-class RAS features for 24/7 mission-critical applications.
- The system is managed by the independent service processor's eXtended System Control Facility (XSCF).
- Firmware updates during system operation are supported.

The Fujitsu M10-4 server is a high-performance, highly reliable midrange server that is ideal for data center integration and virtualization. It can be configured with as many as 64 cores, large memory, and large disk capacity. Processor resources can be expanded incrementally with the CPU Activation feature, which supports adding processor resources one core at a time. Its SPARC64 X (“ten”) processor was developed to deliver dramatic high-speed performance by implementing instructions in hardware that accelerate key software-on-chip functions. The Fujitsu M10-4 server enables highly flexible system configuration with two no-cost virtualization technologies, Oracle VM Server for SPARC and the Oracle Solaris Zones feature of Oracle Solaris.



Protect Your Investment with Reliability, Availability, Serviceability, and Flexibility

The Fujitsu M10-4 server has many mainframe-class reliability, availability, and serviceability (RAS) features, such as automatic recovery with instruction retry, up to 2 TB of system memory with error-correcting code (ECC) protection with extended ECC support, guaranteed data path integrity, and configurable memory mirroring. In addition, the disks, I/O cards, power supplies, and fans are redundant and hot-swappable. To enhance flexibility, multiple independent logical domains can be configured with Oracle VM Server for SPARC. For additional flexibility, multiple Oracle Solaris zones can be configured in logical domains and processor/memory resource allocation can be changed dynamically. Both Oracle VM Server for SPARC and the Oracle Solaris Zones feature of Oracle Solaris are included in all Fujitsu M10 servers at no cost.

Oracle Solaris: The World's Most Advanced Operating System

Only Oracle offers the Oracle Solaris Application Guarantee Program, offering guaranteed binary and source-code compatibility for applications dating back to 1997 or earlier. The Fujitsu M10-4 server supports Oracle Solaris 10 and Oracle Solaris 11. In addition, Oracle Solaris 8 and Oracle Solaris 9 are available to use in Oracle Solaris Legacy Containers. Oracle Solaris 10 also delivers Oracle Solaris ZFS and revolutionary features such as dynamic tracing (DTrace), cryptographic infrastructure, user and process rights management, and the Oracle Solaris IP Filter.

Fujitsu M10-4 Server Specifications	
Processor	
CPU	SPARC64 X 16-core processors, SPARC V9 architecture, ECC-protected
Primary cache per core	64 K data cache and 64 K instruction cache
Secondary cache per processor	24 MB
Clock speed	2.8 GHz
System	
CPU	As many as four CPUs (two CPUs per board/two boards per unit)
Main memory	Up to 2,048 GB, with 32 GB DIMM
I/O	<ul style="list-style-type: none"> • 11 PCI Express 3.0 short, low-profile slots (eight lanes) • As many as 71 PCI Express slots with optional PCI expansion unit • 4-port GbE, 1-port SAS, 2-port USB
Memory bandwidth (per chip)	102 GB/sec
Service processor	One per unit
Storage	
Boot device	As many as eight 600 GB internal 2.5-in. SAS HDDs or 200 GB SAS SSDs
Software	
Operating system	<ul style="list-style-type: none"> • Oracle Solaris 10 • Oracle Solaris 11
Management software	<ul style="list-style-type: none"> • XSCF monitoring/control facility • XSCF software, which manages hardware configuration and health, domain configuration and status, error monitor, and notification
System monitoring	Oracle Enterprise Manager Ops Center
Reliability, Availability, and Serviceability	
Key features	<ul style="list-style-type: none"> • End-to-end ECC protection • Guaranteed data path integrity • Automatic recovery with instruction retry • Dynamic L1 and L2 cache way degradation • ECC and Extended ECC protection for memory, memory mirroring, periodic memory patrol, and predictive self-healing • Hardware redundancy in memory, HDD/SSD, PSU, fan, and liquid cooling pump • Hot-pluggable HDD/SSD, PSU, PCI card, and fan • Live operating system upgrades • Firmware updates during system operation
Environment	
AC power	200 V to 240 V \pm 10% (50/60 Hz)
Operating temperature	<ul style="list-style-type: none"> • 5° to 35° C (41° to 95° F) at an altitude of 0 m to 500 m • 5° to 33° C (41° to 91° F) at an altitude of 501 m to 1,000m • 5° to 31° C (41° to 88° F) at an altitude of 1,001 m to 1,500 m • 5° to 29° C (41° to 84° F) at an altitude of 1,501 m to 3,000 m
Non-operating temperature	<ul style="list-style-type: none"> • -20° to 60° C (packed) • 0° to 50°C (non-packed)
Altitude	Up to 3,000 m (9,843 ft.)

Fujitsu M10-4 Server Specifications – continued	
Dimensions and Weight	
Height	17.5 cm (6.9 in.)
Width	44.0 cm (17.3 in.)
Depth	74.6 cm (29.4 in.)
Weight	58 kg (127.9 lb.)
Regulations	
Safety	<ul style="list-style-type: none"> • UL60950-1, 2nd Edition + A1 • CSA C22.2 No. 60950-1-07 + A1 • EN60950-1:2006 + A1:2010 +A2:2011 • IEC60950-1:2005, 2nd Edition + A1:2009 (evaluated to all CB countries) • CFR21 Part 1040 • IEC60825-1 • IEC60825-2 • CB Scheme with all country deviations • CNS14336&GB4943 through exemption • CNS14336 • S-Mark • GOST-R certification mark
RFI/EMC	<ul style="list-style-type: none"> • EN55022:2010 • VCCI (2012) • FCC Part-15 (2012) • CNS13438:2006 (CISPR 22:2005 +A1:2005) • KCC • GOST-R certification mark • S-Mark • EN61000-3-2:2006 + A1:2009 + A2:2009 • EN61000-3-3:2008 • JIS C 61000-3-2 (2011) • ICES-003 Class A • AS/NZS CISPR 22 (2009) • CISPR 22:2008
Immunity	<ul style="list-style-type: none"> • EN55024:2010 • IEC61000-4-2 • IEC61000-4-3 • IEC61000-4-4 • IEC61000-4-5 • IEC61000-4-6 • IEC61000-4-8 • IEC61000-4-11
Telecommunications	EN 300 386 V1.4.1 (2008)

Warranty

Visit oracle.com/us/support/index.html for Oracle's global warranty support information on Oracle products.

Services

From design and implementation to support and management, Oracle provides an end-to-end portfolio of services designed to accelerate the alignment of IT infrastructure with business needs, optimize usage of IT assets, and contain costs. Oracle's expertise helps you address key data center challenges, including virtualization/consolidation, power, space and cooling optimization, planning and implementation, and ongoing maintenance and support. In addition, Oracle offers top-rated technical support for your Fujitsu M10-4 server. Visit oracle.com/us/support/index.html for information on Oracle's service program offerings for Oracle products.

Contact Us

For more information about the Fujitsu M10-4 server, visit oracle.com or call +1.800.ORACLE1 to speak to an Oracle representative.

 Oracle is committed to developing practices and products that help protect the environment

Copyright © 2013, Oracle and/or its affiliates. All rights reserved. This document is provided for information purposes only, and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document, and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission. Oracle and Java are registered trademarks of Oracle and/or its affiliates. Fujitsu and M10-4 are registered trademarks of Fujitsu and/or its affiliates. Other names may be trademarks of their respective owners. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. UNIX is a registered trademark of The Open Group. 0213

Hardware and Software, Engineered to Work Together